



HIS InterSecure Solutions (S) Pte Ltd

Blk 1092 Lower Delta Road #04-06/07
Tiong Bahru Industrial Estate. Singapore 169203
Tel: (65) 62727375, Fax: (65) 62733073
Website: www.hiss.com.sg

LORD VICTOR SERIES (Victor 1 to Victor 5)

SPECIFICATIONS/FEATURES

European Safe Rating Committee: Burglary Rating Category 9/10

This safe is rated by the European Safe Rating Committee under category 9/10. This rating is used by insurers to determine the insurance cover for items stored in the safe. This rating class is higher than that of Underwriters' Laboratories (UL) TL-15 and European Standard EN1143-1 Grade 1.

BODY

The LORD VICTOR SAFE body measures overall thickness of 4.13" (105mm) approx. incorporating the LORD special designed barrier encased within the steel walls protecting all five sides of the safe body with a single case unit of consistent strength, free of surface seams thus gives the safe body its immense strength and protective qualities, offering great resistance to attack.

DOOR

The overall door thickness measures an impressive 5.66" (144mm) approx. incorporating the LORD special designed barrier encased between heavy steel press formed plates with the lockcase forming an integral part of the door structure. Further, additional security has been achieved from a unique method of anchoring the LORD AP Bar material to eliminate the removal by attackers of the outer door steel.

BOLTWORK

A series of heavy duty 1 1/2" (38mm) running bolts secure the safe door in special reinforced sections within the safe body. Long throw bolts lock directly into the recess of the body (in cup form) for uniform strength between the door & body. Even when the hinges are cut off or under an explosive attack, the door remains securely locked into the body.

LOCKING

The locking mechanism is controlled by one keylock and one 3-wheel combination lock the numbers of which is changeable at will by the user. The combination lock is easy to operate and is capable of one million-code change.

AUTOMATIC DEADLOCKING

The LORD VICTOR series safe is fitted with an automatic deadlocking device that is on guard every time the safe door is locked. This automatic deadlocking system is designed to protect the locked door in the event of an attack by securing the locking bolts for additional protection.

INTERNATIONAL RATING & TESTING STANDARDS

The VICTOR safe is manufactured to well known standards which include the UL standard (Underwriters' Laboratories Incorporation Std USA), SIRIM Standard (for hydraulic Jack Attack) JIS Standard (Japanese Industrial Std) & VDMA (German Standard). Lord Victor safe has also passed 2 ½ hour fire test conducted in Australia.

INTERNAL FITTINGS

Standard fittings include adjustable shelving and a single row of locked drawers. Custom built fittings could be incorporated upon request.

DIMENSIONS

	EXTERNAL			INTERNAL		
	H	W	D	H	W	CLEAR DEPTH
VICTOR 1	667mm	565mm	587mm	457mm	355mm	324 mm
VICTOR 2	870mm	616mm	665 mm	660mm	406mm	400mm
VICTOR 3	1073mm	667mm	742mm	863mm	457mm	476mm
VICTOR 4	1378 mm	743mm	855mm	1168mm	533mm	590mm
VICTOR 5	1658mm	743mm	855 mm	1448 mm	533mm	590mm

SCHEDULE & SIZES

SIZE	STANDARD FITTINGS	INTERIOR HEIGHT <u>Above Drawer</u> <u>Below Drawer</u>	Approximate Nett Weight
VICTOR 1	1 full width Drawer, 1 adjustable shelf 3 moving bolts & 3 fixed bolts	335mm	406 kg
VICTOR 2	2 half width Drawer, 1 adjustable shelf 4 moving bolts & 4 fixed bolts	538mm	599 kg
VICTOR 3	2 half width Drawer, 1 adjustable shelf 4 moving bolts & 4 fixed bolts	741mm	822 kg
VICTOR 4	2 half width Drawer, 2 adjustable shelves 6 moving bolts & 6 fixed bolts	1046mm	1109 kg
VICTOR 5	2 half width Drawer, 2 adjustable shelves 6 moving bolts & 6 fixed bolts	<u>587mm</u> <u>724mm</u>	1398 kg

