

TL-47

TL-47 home safe is tested to provide 60 minutes of fire protection for your paper records in accordance to KSG 4500 standard. It is equipped with dual locking system for both combination and electronic safe

Body: Comprising of international standard steel filled with fireproof mixture

Boltwork: The door is secured by two 20 mm in diameter steel moving bolts at the front end fixed bolts at the rear edge

Locking: The locking mechanism is controlled by one 3-wheel combination lock for TL-47C and electronic lock for TL-47E. The numbers are changeable at will by user.



C-DIAL



DIGITAL

External Dimensions (mm)			Internal Dimensions (mm)			Weight (kg)	Accessory
Height	Width	Depth	Height	Width	Depth		
470	350	430	350	240	290	70	1 Shelf

- Height inclusive of legs
- Depth inclusive of handle



Marketed and Supported by:
HIS InterSecure Solutions (S) Pte Ltd
 203 Henderson Road #02-10
 Wing A, Henderson Industrial Park
 Singapore 159546
 Tel: 6272 7375 Fax : 6273 3073
 Website: www.hiss.com.sg

This Catalogue has been designed for distribution throughout many international markets. Thus, some specifications, comparisons and information set forth herein may vary in all markets. The manufacturer's policy reserved the right to change the specifications without prior notice for continuous improvement.